

Turn- and tilting table

RU-DK-T14/34

Multi-functional assembly table for the sash and frame assembly

Turn- and tilting-table with pneumatically tilting-device. Working-platform with 4 extendable ledges, Basic size 1400 x 1500 mm, extended 3400 x 2500 mm. Contact-surface covered with felt. Tilting table height adjustable from 900 – 1050 mm. 2 mounting plates mounted slide able and fold down.

Optionally accessory:

- Roller conveyor as mounting surface
- column-guided hoist-device 400 mm (thereby horizontal and vertical height-adjustment possible) Flat clamping-cylinder
- sash-assembly device
- driving-device with 4 flange rolls or 4 castors
- 6 swivelling trays with each tray 2 compartments.



Technical Data:

Type	Order- No.	Size working platform	Size platform extended
RU-DK-T14/34	10383000	1400 x 1500 mm	3400 x 2500 mm
Rolls-conveyor as mounting surface	6449		
Hoist device 400 mm, column guided	6450		
Flat clamping-cylinder with hand valve, clamping-range 130 mm	6451		
Sash-assembly-device	6452		
Driving device with 4 castors	6453		
Driving device with 4 flange rolls and fixing brake	6454		
Guiding rail for transport system, 3 double metres	6354		
6 trays with 2 compartments	6455		